

REVISIONS

LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Added one vendor, CAGE 1ES66. Made changes to table I and figure 1. Editorial changes throughout.	91-10-29	M.A. Frye

REV																				
SHEET																				
REV																				
SHEET																				
REV STATUS OF SHEETS	REV	A	A	A	A	A	A	A	A											
	SHEET	1	2	3	4	5	6	7												

PMIC N/A	PREPARED BY Rick C. Officer	DEFENSE ELECTRONIC SUPPLY CENTER DAYTON, OHIO 45444		
STANDARD MILITARY DRAWING THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE AMSC N/A	CHECKED BY Charles E. Besore			
	APPROVED BY Michael A. Frye			
	DRAWING APPROVAL DATE 89-07-17			
	REVISION LEVEL A	SIZE A	CAGE CODE 67268	5962-89581
	SHEET	1	OF	

1. SCOPE

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

1.2 Part or Identifying Number (PIN). The complete PIN shall be as shown in the following example:



1.2.1 Device type(s). The device type(s) shall identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	REF01A	Precision reference +10-volt adjustable output
02	REF01	Precision reference +10-volt adjustable output

1.2.2 Case outline(s). The case outline(s) shall be as designated in appendix C of MIL-M-38510, and as follows:

<u>Outline letter</u>	<u>Case outline</u>
G	A-1 (8-lead, .370" x .185"), can package
P	D-4 (8-lead, .405" x .310" x .200"), dual-in-line package
2	C-2 (20-terminal, .358" x .358" x .100"), square chip carrier package

1.3 Absolute maximum ratings.

Input voltage (V_{IN})	-----	40 V dc
Power dissipation (P_D)	-----	500 mW ^{1/}
Output short circuit duration	-----	Indefinite
Storage temperature	-----	-65° C to +150° C
Lead temperature (soldering, 10 seconds)	-----	+300° C
Junction temperature (T_J)	-----	+150° C
Thermal resistance, junction-to-case (Θ_{JC})	-----	See MIL-M-38510, appendix C

1.4 Recommended operating conditions.

Ambient operating temperature range (T_A) ----- -55° C to +125° C

^{1/} Derate above +80° C, 7.1 mW/° C for case outline G. Derate above +75° C, 6.6 mW/° C for case outline P. Derate above +72° C, 7.8 mW/° C for case outline 2.

STANDARD MILITARY DRAWING DEFENSE ELECTRONIC SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89581
		REVISION LEVEL A	SHEET 2

2. APPLICABLE DOCUMENTS

2.1 Government specification, standard, and bulletin. Unless otherwise specified, the following specification, standard, and bulletin of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

BULLETIN

MILITARY

MIL-BUL-103 - List of Standardized Military Drawings (SMD's).

(Copies of the specification, standard, and bulletin required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Case outline(s). The case outline(s) shall be in accordance with 1.2.2 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.3 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in table I and shall apply over the full ambient operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are described in table I.

3.5 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked as listed in MIL-BUL-103 (see 6.6 herein).

STANDARD MILITARY DRAWING DEFENSE ELECTRONIC SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89581
		REVISION LEVEL A	SHEET 3

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions ^{1/} -55° C ≤ T _A ≤ +125° C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Quiescent supply current	I _{SY}	No load	1	All		1.4	mA
			2, 3		2.0		
Output adjustment range	ΔV _{TRIM}	R _p = 10 kΩ, T _A = +25° C	1	All	±3.0		%
Output voltage	V _{OUT}	I _L = 0 mA	1	01	9.97	10.03	V
				02	9.95	10.05	
			2, 3	01	9.95	10.04	
				02	9.905	10.095	
Short circuit current	I _{OS}	V ₀ = 0 V, T _A = +25° C	1	01	+15	+60	mA
Sink current	I _S	T _A = +25° C	1	All	-0.3		mA
Load regulation	LD reg	I _L = 0 to 10 mA ^{2/ 3/}	1	01		0.008	%mA
				02		0.010	
		I _L = 0 to 8 mA ^{2/ 3/}	2, 3	01		0.012	
				02		0.015	
Line regulation	LN reg	V _{IN} = 13 V to 33 V ^{2/}	1	All		0.01	%V
		V _{IN} = 13 V to 33 V ^{2/}	2, 3	All		0.015	
Load current	I _L	T _A = +25° C ^{4/}	1	All	10		mA
			2, 3		8		
Output voltage noise	e _{n p-p}	0.1 Hz to 10 Hz	4	All		30	μV p-p
Output voltage temperature coefficient	TCVO	-55° C ≤ T _A ≤ +125° C ^{5/}	5, 6	01		±8.5	ppm/ ° C
				02		±25	

- ^{1/} V_{IN} = 15 V.
^{2/} Line and load regulation specifications include the effect of self-heating.
^{3/} LD_{reg} = ΔI_L/ΔV_{OUT} × 100.
^{4/} Minimum load current guaranteed by load regulation test.
^{5/} TCVO = ABS|V_{MAX} - V_{MIN}| / (10 V) (-55° C to +125° C) / 180° C × 10⁶.

**STANDARD
 MILITARY DRAWING
 DEFENSE ELECTRONIC SUPPLY CENTER
 DAYTON, OHIO 45444**

**SIZE
 A**

5962-89581

REVISION LEVEL
 A

SHEET
 4

Device types	01 and 02	
Case outlines	G and P	2
Terminal number	Terminal symbol	
1	NC	NC
2	V _{IN}	NC
3	NC	NC
4	GND	NC
5	TRIM	V _{IN}
6	V _{OUT}	NC
7	NC	NC
8	NC	NC
9	---	NC
10	---	GND
11	---	NC
12	---	TRIM
13	---	NC
14	---	NC
15	---	V _{OUT}
16	---	NC
17	---	NC
18	---	NC
19	---	NC
20	---	NC

NC = No connection

FIGURE 1. Terminal connections.

STANDARD MILITARY DRAWING DEFENSE ELECTRONIC SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89581
		REVISION LEVEL A	SHEET 5

3.6 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-BUL-103 (see 6.6 herein). The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall affirm that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.7 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.9 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

- a. Burn-in test, method 1015 of MIL-STD-883.
 - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.6 herein).
 - (2) $T_A = +125^\circ\text{C}$, minimum.
- b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 7, 8, 9, 10, and 11 in table I, method 5005 of MIL-STD-883 shall be omitted.

4.3.2 Groups C and D inspections.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test conditions, method 1005 of MIL-STD-883.
 - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.6 herein).
 - (2) $T_A = +125^\circ\text{C}$, minimum.
 - (3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

STANDARD MILITARY DRAWING DEFENSE ELECTRONIC SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89581
		REVISION LEVEL A	SHEET 6

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	1, 2, 3
Final electrical test parameters (method 5004)	1*, 2, 3, 4
Group A test requirements (method 5005)	1, 2, 3, 4, 5, 6
Groups C and D end-point electrical parameters (method 5005)	1, 2, 3

* PDA applies to subgroup 1.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished in accordance with MIL-STD-481 using DD Form 1693, Engineering Change Proposal (Short Form).

6.4 Record of users. Military and industrial users shall inform Defense Electronics Supply Center when a system application requires configuration control and the applicable SMD. DESC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronics devices (FSC 5962) should contact DESC-ECS, telephone (513) 296-6022.

6.5 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone (513) 296-5375.

6.6 Approved sources of supply. Approved sources of supply are listed in MIL-BUL-103. The vendors listed in MIL-BUL-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DESC-ECS.

STANDARD MILITARY DRAWING DEFENSE ELECTRONIC SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-89581
		REVISION LEVEL A	SHEET 7

STANDARDIZED MILITARY DRAWING SOURCE APPROVAL BULLETIN

DATE:

Approved sources of supply for SMD 5962-89581 are listed below for immediate acquisition only and shall be added to MIL-BUL-103 during the next revision. MIL-BUL-103 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DESC-ECS. This bulletin is superseded by the next dated revision of MIL-BUL-103.

Standardized military drawing PIN	Vendor CAGE number	Vendor similar PIN <u>1/</u>
5962-8958101GX	06665 07933 1ES66 64155	REF01AJ/883C REF01AT/883B REF01AJ/883B REF01AH/883B
5962-8958101PX	06665 07933 1ES66 64155	REF01AZ/883C REF01ADE/883B REF01AZ/883B REF01AJ8/883B
5962-89581012X	06665	REF01ARC/883C
5962-8958102GX	06665 07933 1ES66	REF01J/883C REF01T/883B REF01J/883B
5962-8958102PX	06665 07933 1ES66	REF01Z/883C REF01DE/883B REF01Z/883B
5962-89581022X	06665	REF01RC/883C

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

<u>Vendor CAGE number</u>	<u>Vendor name and address</u>
06665	Analog Devices, Incorporated Precision Monolithic Division 1500 Space Park Drive P.O. Box 58020 Santa Clara, CA 95052-8020
07933	Raytheon Company Semiconductor Division 350 Ellis Street P.O. Box 7016 Mountain View, CA 94039-7016
1ES66	Maxim Integrated Products, Incorporated 120 San Gabriel Drive Sunnyvale, CA 94086
64155	Linear Technology Corporation 1630 McCarthy Boulevard Milpitas, CA 95035-7487

<p>The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in this information bulletin.</p>
--